

Only \$54,245

Usually \$60,275

Code: PRIOEH320-BASE

EH320-BASE

suitable for non-vacuum
sterilisation runs
5 program memory

Only \$61,200

Usually \$68,002

Code: PRIOEH320-SMART

EH320-SMART

vacuum options: pre-cycle, cooling
and drying but can be used without
10 program memory

Export Crate

Code PRIOPC/AEC/020 **Only \$2,675** | Usually \$2,973

Complying with AS/NZS standards, the unit has ASME-certified 316L stainless steel chamber and is inherently safe with thermal and pressure interlocks.



Many options and accessories available including loading trolleys, loading cassettes, printer, wandering probe, discard containers, water softener etc.

Please contact us for a site visit to assist in configuring your autoclave to your requirements.

- Operation up to 140°C / 2.5 Bar
- Chamber Dimensions: 630mm Ø x 1,025mm deep
- Water cooled drain protection as standard
- Quickseal single-action door fitted with thermal and pressure locks to prevent opening at load temperature above 80°C and pressures above 0.2 bar
- TACTROL 3 microprocessor control system with simple and fully variable setting of process time, temperature and with graphic indication of cycle status
- USB port for logging, remote diagnosis and updating
- Large cylindrical chamber within a compact frame
- Automatic water filling
- Low water level sensor
- Forced air cooling as standard helping to reduce cycle times
- Automatic timed and pulsed free steaming as standard for improved air removal and sterilising performance
- Steam generated within the chamber (electrically heated model)
- Complete with thermocouple entry and test ports
- Delayed start and media warming function as standard for ready to pour media at the start of the day
- Epoxy coated panels and frame members are treated with an anti-bacterial agent which is effective against all bacteria and fungi including MRSA
- Pressure vessel carries a 10-year warranty and is insurance approved