

150L Front Loading Autoclave

Complying with AS/NZS standards, the unit has grade 316L stainless steel chamber and is inherently safe with thermal and pressure interlocks.



- Operation up to 140C - 2.5 Bar
- 5 program memory
- Water cooled drain protection as standard
- Quickseal single-action door fitted with thermal and pressure locks to prevent opening at load temperature above 80 °C and pressures above 0.2 bar
- TACTROL 3 microprocessor control system with simple and fully variable setting of process time, temperature and with graphic indication of cycle status.
- Large cylindrical chamber within a compact frame
- Forced air cooling as standard helps to reduce cycle times
- Automatic timed & pulsed free steaming as standard for improved air removal and sterilising performance
- Steam generated within the chamber (electrically heated model)
- Complete with thermocouple entry and test ports
- Delayed start and media warming function as standard for ready-to-pour media at the start of the day
- Low water level sensor
- Epoxy-coated panels and frame members are treated with an anti-bacterial agent which is effective against all bacteria and fungi including MRSA
- 2-year warranty with the chamber and pressure vessel* carrying a 10-year warranty (* insurance approved)

Only \$39,520

Usually \$43,912

Model EH150-BASE with cylindrical 150L chamber

Includes: 2 non-tilting removable shelves and Export Crate

Code: PRIOEH150-BASE



Chamber Size
500mm Ø
740mm Depth

A variety of optional accessories are available, including loading trolleys, discard containers, printers, wandering probes, and water softeners. Contact us today for assistance in configuring your autoclave solution.